

COLLECTION: NIGHTMOON

DESIGN: NIGHTMOON

BASIC INFORMATIONS

Brand	Bru	Number of colour ways	28
Tariff item number	5903909900	MID	CNHANLON2150HAN
Country of origin	China	Characteristics	Blackout
Vertical repeat cm	Plain	Vertical repeat inch	Plain
Horizontal repeat cm	Plain	Horizontal repeat inch	Plain
Face out	Yes	Full roll diameter cm	18
Full roll diameter inch	7.09	Average piece length m	50
Minimum for special colour m	1000	Delivery time weeks special lab dip	2
Suspended box	Yes		

CARE CODES



CARE AND USAGE

Care code comments

Drip dry

Use codes

Curtains	Yes	Curtains and draperies	Yes
Bed covering	Yes	Accessories	Yes

ENVIRONMENTAL STANDARDS



**STANDARD
100**
2111231
Centexbel



Labels

There are no technical details for this section.

COLLECTION: NIGHTMOON

DESIGN: NIGHTMOON

FR STANDARDS

British BS 5867 part 2 type B	Yes	American CAL 117	Yes
Canadian ULC S109 large flame	Yes	Canadian ULC S109 small flame	Yes
German B1 DIN 4102	Yes	European EN 13773	Yes
MVSS 302	Yes	IMO FTPC part 7 drapery	Yes
French NF P92-503 507	Yes	American NFPA 260	Yes
American NFPA 701 2010	Yes	Taiwanese CNS10285-L31961	Yes

FABRIC SPECIFICATIONS

Composition	61% Polyacrylic, 27% Recycled Polyester, 12% Polyester	Average yarn number	23.61
Composition fabric	70% Recycled Polyester, 30% Polyester	Composition coating	100% Polyacrylic
Construction	56x29	Woven	Yes
Useable width cm	138	Useable width inch	54.33
Full width cm	140	Full width inch	55.12
Weight g/m²	360	Thickness mm	0.730
Colouring type	Piece dyed	Filament or staple	100% filament
Textured or non textured	100% not textured		

Treatment

Flame retardant	Yes	Backing	Yes
-----------------	-----	---------	-----

Type of finish

There are no technical details for this section.

Type of print or dye

Disperse	Yes
----------	-----

Weaving type

Plain	Yes
-------	-----

COLLECTION: NIGHTMOON

DESIGN: NIGHTMOON

MECHANICAL PERFORMANCE

Martindale rubs	20,000	Colour fastness to light	4
Wyzenbeek double rubs	68,800	Pilling	4
Brush pilling	4	Wyzenbeek wire screen double rubs	15,000
Wyzenbeek cotton duck double rubs	68,800	Acoustic absorption ISO 354 - ISO 11654	D
Wyzenbeek wire screen heavy duty	Yes		

Colour fastness to light – ISO 105-B02

Colour fastness to light	4
--------------------------	---

Colour fastness to weathering – ISO 105-B04:1994

There are no technical details for this section.

Colour fastness to water – ISO 105-E01

Colour fastness to water	5
--------------------------	---

Colour fastness to dry rub – ISO 105-X12

Colour fastness dry rub	4-5
-------------------------	-----

Colour fastness to wet rub – ISO 105-X12

Colour fastness wet rub	4-5
-------------------------	-----

Tearing strength – ISO 13937-3

Tearing strength warp N	57	Tearing strength weft N	38
-------------------------	----	-------------------------	----

Tensile strength – ISO 13934-1

Tensile strength warp N/5cm	920	Tensile strength weft N/5cm	870
-----------------------------	-----	-----------------------------	-----

Elongation – ISO 13934-1

Elongation warp %	28.5	Elongation weft %	34
-------------------	------	-------------------	----

Seam slippage – ISO 13936-2

Seam slippage warp mm	2	Seam slippage weft mm	2
-----------------------	---	-----------------------	---

Dimensional stability (indicated in %) – ISO 3759

Dimensional change warp	-0.14	Dimensional change warp after ironing with steam	-0.27
Dimensional change warp after ironing without steam	0.00	Dimensional change weft	-0.23
Dimensional change weft after ironing with steam	0.33	Dimensional change weft after ironing without steam	0.07

COLLECTION: NIGHTMOON

DESIGN: NIGHTMOON

WASHABILITY

Resistance to domestic washing 30° C, indicated in % - ISO 6330

Dimensional change warp	-0.96	Dimensional change warp after ironing	-0.93
Dimensional change weft	-1.43	Dimensional change weft after ironing	-1.53
Colour fastness ISO 105 C06	4-5		

Resistance to domestic washing 40° C, indicated in % - ISO 6330

There are no technical details for this section.

Resistance to domestic washing 60°C, indicated in % - ISO 6330

Dimensional change warp	-2.42	Dimensional change warp after ironing	-2.32
Dimensional change weft	-2.86	Dimensional change weft after ironing	-2.86
Colour fastness ISO 105 C06	5		

Resistance to domestic washing 74 C ISO 6330

Dimensional change warp	0.00	Dimensional change warp after ironing	0.00
Dimensional change weft	0.00	Dimensional change weft after ironing	0.00

Resistance to dry cleaning P, indicated in % - ISO 105 D01

Dimensional change warp	-1.76	Dimensional change warp after ironing	-2.79
Dimensional change weft	-2.72	Dimensional change weft after ironing	-2.79
Colour fastness ISO 105 D01	5		

CONSTRUCTION

Yarn 1

Warp Composition	65% Polyester, 35% Recycled Polyester	Warp Is Filament	Yes
Warp Is Not High Tenacity	Yes	Warp Is Staple	No
Warp Sizes	75D	Warp Textured	No
Warp Threads per cm	56	Warp TPM	0

Yarn 2

Weft Composition	65% Polyester, 35% Recycled Polyester	Weft Is Filament	Yes
Weft Is Not High Tenacity	Yes	Weft Is Staple	No
Weft Sizes	300D	Weft Textured	No
Weft Threads per cm	29	Weft TPM	0

COLLECTION: NIGHTMOON

DESIGN: NIGHTMOON

DOWNLOADS

-  [NIGHTMOON-FMVSS302-40892](#)
-  [Nightmoon - B1](#)
-  [Nightmoon Taiwanese CNS 10285 L3196](#)
-  [Nightmoon - FMVSS302-40892](#)
-  [202301174-EN_Nightmoon](#)
-  [Nightmoon - CAN ULC S109-42935](#)
-  [202301176-IMO_Nightmoon](#)
-  [Nightmoon - 202301174-EN](#)
-  [Nightmoon - Cal TB 117-2013-40892](#)
-  [NIGHTMOON-Cal TB 117-2013-40892](#)
-  [Nightmoon - 202301177-M1](#)
-  [Nightmoon - NFPA 260 UFAC-40892](#)
-  [Nightmoon - NFPA701](#)
-  [NIGHTMOON-NFPA 260 UFAC-40892](#)
-  [Nightmoon-CAN ULC S109-42935](#)
-  [Nightmoon - 202301177-M1 FAIL](#)
-  [Nightmoon - 202301176-IMO](#)

